


HANGING EQUIPMENT

For the purpose of hanging equipment weighing more than 10 lbs.

Shelter Works fiberglass enclosures are custom manufactured for each project.



Some walls contain visible wood reinforcement within the walls for mounting heavy equipment. (see left)

Some walls have invisible wood reinforcement throughout.

Some walls have no reinforcement and should not have heavy equipment mounted directly on them.

If you are unsure whether your shelter has the proper wall reinforcement for hanging items weighing 10 lbs or more, please contact Shelter Works, with your shelter number, to find out.

For temporary equipment, we recommend installing U-Channel supports, using a #14 type screw every 12" to 6", depending on the weight.

For equipment that will be permanently installed in the building, we recommend using the following types of screws:

Diameter/Thread Size: #14-10 Drive: Slotted Grade: 18-8 Head: Indented Hex Washer Length: 1" Material: Stainless Steel Point: Type A Type: Sheet Metal Screw Fastenal Part #: 73153

Diameter/Thread Size: #10-16 Drive: Unslotted Grade: 410 Head: Indented Hex Washer Length: 1-1/2" Material: Stainless Steel Point: #3 Type: Self-Drilling Screw Fastenal Part #: 31954

For questions or additional information, contact Shelter Works at (800) 794-8037.

